

## Technical Bulletin

### DYNAX DX4000 FLUROSURFACTANT

Dynax DX4000 is a highly effective and efficient product, especially designed to provide rapid spreading, wetting and leveling performance to various water-based coating systems, such as paints, inks, floor polishes, etc., on low surface tension substrates that are difficult to wet out. DX4000 provides both superior dynamic and equilibrium surface tensions compared to conventional surfactants including fluorochemical and silicone surfactants: it quickly lowers the surface tension of aqueous solutions down to 16 dynes/cm at a very low concentration. DX4000 can be used without a defoaming agent because of its low foaming tendency.

#### Typical Properties<sup>1</sup>

Appearance	Clear, liquid
Ionic Character	Slightly cationic
Composition	34.0-36.0% Actives 10-15% Hexylene glycol Remainder: water
Density	1.17 g/ml (@25°C)
Viscosity	20-40 cP's (Brookfield DV-E spindle #3, speed 50, temp. 25°C)
Flammability	Non Flammable
pH	6.0 - 7.0
Solubility	DX4000 can be diluted directly in water.
Stability	At least one year if stored in original containers at temperatures not exceeding 50°C (122°F).
Storage	DX4000 is chemically stable, but should be stored at temperatures above 10°C. If frozen, warm the product to room temperature and mix it well before use. Freezing should not affect the properties of the product or its performance.

<sup>1</sup> Not for specifications

### **Dynamic Surface Tension Data (@0.1% actives in water)\***

<b>Surface Age (Seconds)</b>	<b>Surface Tension (dyne/cm)</b>
0.005	21.1
0.051	19.5
0.52	17.8
5.2	16.7
Equilibrium	16.6

\*Dynamic surface tensions were measured using Kruss Bubble Pressure Tensiometer BP2

### **Surface Tension Data**

<b>% Actives in distilled water</b>	<b>Surface Tension (dyne/cm)</b>
0.1	15.7
0.01	16.0
0.001	21.0

By Wilhelmy Plate Method: KRÜSS Force Tensiometer K100C

### **Product Safety**

DX4000 is not derived from PFOS (Perfluorooctyl Sulfonate) or from PFOA (Perfluorooctanoic Acid). DX4000 does not degrade into PFOS or PFOA. DX4000 meets the objectives of the US EPA 2010/15 PFOA Stewardship Program.

DX4000 is a minimal skin irritant.  
DX4000 is a minimal irritant to eyes.  
The acute oral LD<sub>50</sub> of albino rats is greater than 5,000 mg/kg.

### **Precautions and First Aid**

DX4000 should be handled with good industrial precautions. Safety goggles and rubber gloves, as well as protective clothing suitable to avoid skin contact should be worn. In case of contact with eyes, flush eyes with plenty of water and consult a physician. In case of skin contact, wash skin with plenty of water and soap.

*Important Notice to Purchaser:* All statements, technical information and recommendations contained herein are based on information and tests we believe to be reliable. The accuracy or completeness thereof is not guaranteed. Since conditions of use are outside our control, the purchaser should determine the suitability of the product for his intended use and assumes all risk and liability in connection therewith.

\*\*\*